

Danish Oil

Wood restoration and finishing oil

Danish Oil is used for the restoration and finishing of furniture and woodwork. Danish Oil can also be used to refresh old varnishes and dull lacquer. It provides a resistant satin finish.

Preparation

Stir the content thoroughly. **On varnished and lacquered wood:**

Clean

with oil thinner and a 00 steel wool. **On raw wood:** Sand evenly with 120 grit sandpaper and dust off the surface.

Application

Apply a generous oil coat with a stain pad or a cotton rag. **After 15 to 30 minutes, remove any excess oil by rubbing the surface with a cotton cloth.** Between coats, after 24 hours, do a slight polish with a 0000 steel wool or an 800 grit sandpaper.

Number of coat

3 coats

Drying time

- Between coats : 24 hours
- Utilization : 2 days
- First damp cleaning : 14 days

Covering

120 to 250 sq ft / L

Tools cleaning

Oil thinner

Compatibility

Compatible with most varnishes, stains, lacquers and oils.

Incompatible with paint. It's strongly recommended reading carefully the technical sheet of the product and making prior test to ensure the propriety and compatibility of the products.

Residues Disposal

Consult your municipality for proper disposal procedure of this product residues.

Caution



- Adheres to old varnishes and lacquers
- Water resistant
- Easy application
- Easy maintenance
- Satin finish

Project types

Old and modern furniture

Surface types

Wood, Varnished or Lacquered wood, Cork

Composition

Linseed oil, soybean oil, ester of colophony resin, hydro-treated kerosene

VOC

445 g / L

Durability

2 to 5 years

Maintenance

Clean with a oil based soap. After 1 to 2 years, if the finish becomes dull, apply one coat of oil **and wipe off any excess.**

Color

Ventilate well. Wear protective gloves and safety glasses.

CONTENTS HARMFUL - DANGEROUS FUMES FORM WHEN MIXED WITH OTHER PRODUCTS - MAY IRRITATE SKIN - MAY IRRITATE EYES - DANGER OF COMBUSTION - Do not mix with other household chemicals. Do not swallow. Do not breathe fumes. Do not get on skin or clothing. Do not get in eyes. Keep out of reach of children. Wear a mask. Use only in a well-ventilated area. Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard. Keep away from flames or sparks.
FIRST AID TREATMENT Contains Hydrotreated kerosene; Linseed oil; Soybean oil. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

Warranty

Tembi products guarantee the quality of its products. They comply with the description given in the data sheets and proper labels for their intended use, in accordance with the instructions indicated by the company. However, since the manufacturer has no control over the circumstances, methods and usage conditions, this warranty covers only the high quality of Finico products.

Colorless

Aspect

Liquid slightly amber

Sizes

- 946 ml
- 3.78 L

Storage

Keep in an hermetic container at room temperature.

Conservation

3 years

Origin

U.S.A