Page: 1

### MATERIAL SAFETY DATA SHEET

Date Printed: 12/2/2009 Product Name: EPOXY PUTTY STICK NATURAL MAPLE











## 1. COMPANY IDENTIFICATION

Suppliers Name: RPM, WFG.

3194 Hickory Blvd. Hudson, NC 28638 Phone: 828-728-8266

CHEMTREC: (800) 424-9300 International: 703-527-3887 (collect)

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

Component/Exposure Limits	CAS#	% by Wt.	
Diglycidyl Ether of Bisphenol A INGESTION LD(50): >5000 mg/kg (rat)	25068-38-6	15% to 40%	
SKIN ABSORPTION: 20000 mg/kg (rabbit)			
Diglycidyl Ether of Bisphenol A INGESTION LD(50): >5000 mg/kg	25036-25-3	3% to 7%	
SKIN LD(50): 20000 mg/kg (rabbit)			
2,4,6-TRIS (DIMETHYLAMINO) METHYL PHENOL SKIN IRRITATION: 8 (scale 0-8) (rabbit)	90-72-2	1% to 5%	
ORAL LD(50): 1653 mg/kg (rat)			
<pre>INHALATION LC(50): &gt;0.5 mg/L (rat)</pre>			
EYE IRRITATION: 110 (scale 0-110) (rabbit)			
DOT CORROSIVITY: neg. (rabbit)			

### 3. HAZARDS IDENTIFICATION

## Potential Health Effects

## EYE:

May cause moderate eye irritation.

# SKIN:

Has caused allergic skin reactions in humans. A single exposure not likely to cause skin irritation. Prolonged and repeated contact may cause skin irritation with local redness.

## INGESTION:

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

### INHALATION:

## MATERIAL SAFETY DATA SHEET

Product Code: B743-1580

Page: 2

Date Printed: 12/2/2009 Product Name: EPOXY PUTTY STICK NATURAL MAPLE











Vapors are unlikely due to physical properties.

### CHRONIC (CANCER) INFORMATION:

N/A

### TERATOLOGY (BIRTH DEFECT) INFORMATION:

N/A

### REPRODUCTION INFORMATION:

N/A

#### 4. FIRST AID MEASURES

### EYES:

Flush eyes thoroughly with water for several minutes. If effects occur, consult a physician, preferably an opthalmologist.

### SKIN:

Wash skin with plenty of soap and water.

## INGESTION:

No emergency medical treatment necessary.

### INHALATION:

N/A

### NOTE TO PHYSICIANS:

Consider additional thorough skin wash with mild, non-abrasive soap and plenty of warm water for at least fifteen minutes.

## 5. FIRE FIGHTING MEASURES

### FLAMMABLE PROPERTIES:

FLASH POINT: > 140F Method: N/A

### FLAMMABLE LIMITS:

Lower flammable limit: N/A Upper flammable limit: N/A

## **AUTOIGNITION TEMPERATURE:**

N/A

### HAZARDOUS COMBUSTION PRODUCTS:

Carbon dioxide, carbon monoxide, oxides of nitrogen and sulfur.

## EXTINGUISHING MEDIA:

FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

MATERIAL SAFETY DATA SHEET

Date Printed: 12/2/2009 Product Name: EPOXY PUTTY STICK NATURAL MAPLE











## FIREFIGHTING INSTRUCTIONS:

Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be used except as fog to keep nearby containers cool.

Fire Fighters and others who may be exposed to the products of combustion should be equipped with NIOSH approved positive pressure self-contained breathing apparatus (SCBA) and full protective clothing.

#### 6. ACCIDENTAL RELEASE MEASURES

#### SPILLS:

Dispose of in normal manner in accordance to all applicable state, federal, and local laws. Not a hazardous waste.

### 7. HANDLING AND STORAGE

### HANDLING:

No special precautions needed.

Personal hygiene- Wash thoroughly after handling, especially before eating, drinking, smoking, and using restroom facilities. Professionally launder contaminated clothing before use. Empty container precautions- Do not reuse empty containers for food, clothing, or products for human or animal consumption, or where skin contact can occur.

### STORAGE:

Temperature-Less than 90 F. Conditions- Store in cool, dry, well-ventilated area.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### ENGINEERING CONTROLS:

Local exhaust: Use to keep exposures below recommendations. Use if material is heated above 100 F.

## RESPIRATORY PROTECTION:

None required in a well-ventilated area.

### SKIN PROTECTION:

Appropriate impervious gloves. Because a variety of protective gloves exist, consult glove manufacturer to determine the proper type for the specific operation.

Page: 3

Product Code: B743-1580

Page: 4

Date Printed: 12/2/2009 Product Name: EPOXY PUTTY STICK NATURAL MAPLE











## EYE PROTECTION:

Safety glasses or goggles.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT: N/A MELTING POINT: N/A VAPOR PRESSURE: N/A VAPOR DENSITY: N/A

SOLUBILITY IN WATER: Insoluble in water

SPECIFIC GRAVITY: .941

pH: N/A

VOLATILE ORGANIC COMPOUNDS: <0.1%

ODOR: Mercaptan/sulfur

APPEARANCE: Putty

## 10. STABILITY AND REACTIVITY

## CHEMICAL STABILITY (CONDITIONS TO AVOID):

This product is stable.

### INCOMPATIBILITY:

None.

## HAZARDOUS DECOMPOSITION PRODUCTS:

Carbon dioxide, aldehydes, acids, oxides of sulfur and nitrogen

#### HAZARDOUS POLYMERIZATION:

Will not occur.

## 11. TOXICOLOGICAL INFORMATION

EYE: N/A

SKIN: N/A

INGESTION: N/A

INHALATION: N/A

SUBCHRONIC: N/A

CHRONIC/CARCINOGENICITY: N/A

TERATOLOGY: N/A

REPRODUCTION: N/A

MUTAGENICITY: N/A

Page: 5

Date Printed: 12/2/2009 Product Name: EPOXY PUTTY STICK NATURAL MAPLE











### 12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: N/A

CHEMICAL FATE INFORMATION: N/A

### 13. DISPOSAL CONSIDERATIONS

Incinerate in furnace or bury in landfill in accordance with all applicable regulations.

Not classified as a hazardous waste.

### 14. TRANSPORT INFORMATION

Not DOT regulated.

### 15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: TSCA: All ingredients are TSCA listed.

OSHA: Not OSHA regulated.

CERCLA: SARA HAZARD CATEGORY: Not regulated.

SECTION 313: Not regulated.

INTERNATIONAL REGULATIONS:

CANADIAN WHMIS: DB2 skin sensitizer.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA): N/A

EINECS: EINECS listed.

### STATE REGULATIONS:

CALIFORNIA PROPOSITION 65

This product contains the following chemicals known to the state of California to cause cancer or reproductive toxicity

None

The following ingredients are present in this material and are subject to reporting in accordance to the Pennsylvania, New Jersey, and/or Massachusetts Right-to-Know (RTK) laws:

Page: 6

### MATERIAL SAFETY DATA SHEET

Date Printed: 12/2/2009 Product Name: EPOXY PUTTY STICK NATURAL MAPLE











Magnesium Silicate Hydrate (CAS 14807-96-6) Polyether Polymercaptan (Trade Secret) Sodium Calcium Magnesium Silicate (CAS 65997-17-3)

(Not meant to be an all inclusive list - contact PSI for further information)

### 16. OTHER INFORMATION

Hazard Ratings

NFPA Ratings: Health: 1 Fire: 0 Physical Data: 0 PPE: B

MSDS Last Revised: 01/28/08 Created by: I. David Crossan

USERS RESPONSIBILITY: A bulletin such as this cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects on an individual operation should be examined to determined if, or where, precautions — in addition to those described herein — are required. Any health hazard and safety information herein should be passed on to your customers or employees as the case may be

IMPORTANT: WHILE THE DESCRIPTIONS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU PERFORM AN ASSESSMENT TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED, DATA OR INFORMATION SET FORTH. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, OR DATA PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, THE DESCRIPTIONS, DATA AND INFORMATION FURNISHED HEREUNDER ARE GIVEN GRATIS. NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DATA AND INFORMATION GIVEN ARE ASSUMED. ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.