

Technical Data Sheet

Uno

Colored oil for wooden floors

Uno is a colored oil designed to be applied on floors or other wood surfaces. Uno must be covered with Secondo floor oil.

Preparation

Shake well before and while using. Apply at a temperature above 15 °C. Wood must be sanded with 100 or 120 grit sandpaper. Vacuum to dust off. **Prior to application on maple wood**, wet the wood, let dry 2 hours and sand lightly with a 220 grit sandpaper.

It's possible to mix colors. To decrease color intensity, it's possible to mix the colored Uno with the natural Uno.

Application

Apply with a stain applicator, a cloth or a stain pad. **After 5 to 15 minutes, completely wipe off with a cloth to remove any excess oil.**

Number of Coats

1 coat

For a more intense color, it is possible to apply a second coat after 24 hours.

Drying Time

24 hours

Covering

150 to 300 sq ft / L

Tools Cleaning

Oil thinner

VOCs

430 g / L

Storage

Keep in an airtight container.

Residues Disposal

Consult your municipality for proper disposal procedure of this product residues.



- Prevents wood discoloration
- Available in 16 colors
- Great coverage
- Leaves no film on the wood surface
- Lets the wood vein show through
- Easy to apply
- Easy care
- Lets the wood breathe
- Low odor

Project Types

Floors, furniture, kitchen cabinets, countertops, islets, interior windows and doors, woodwork, walls and ceilings

Surface Types

Wood, cork

Compatibility

- Can be applied on: Wood stain
- Can be covered with: Wood oil, wood varnish, wood wax

Sizes

- 20 ml (sample)
- 237 ml
- 946 ml
- 3.78 L
- 18.9 L

DANGER OF COMBUSTION - Keep out of reach of children.
Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

Warranty

Tembi products guarantee the quality of its products. They comply with the description given in the data sheets and proper labels for their intended use, in accordance with the instructions indicated by the company. However, since the manufacturer has no control over the circumstances, methods and usage conditions, this warranty covers only the high quality of Prato-Verde products.

Composition

Safflower oil, tung oil, linseed oil, isoparaffin, iron oxide, siccative.

Origin

Italy

Colors

- 00 - Natural
- 01 - Cherry
- 02 - Rosewood
- 03 - Medium Oak
- 04 - Charcoal
- 06 - Red Fox
- 08 - American Walnut
- 09 - Cinnamon
- 10 - Africajou
- 11- Choco Wood
- 13 - Maple Brown
- 15 - Dark Oak
- 17- Old Pine
- 19 - White
- 20 - Cappuccino
- 21- Grey