---



### Safety Data Sheet according to HPR, Schedule 1

Printing date 11/15/2017

Reviewed on 08/28/2017

1.1 Product identifier	
Trade name:	Polyx®-Oil
Article number:	3031 clear matt, 3043 clear satin
Application of the substance /	the
mixture	Paint
1.3 Details of the supplier of t	he safety data sheet
Manufacturer/Supplier:	Supplier:
	Osmo Wood and Colour Canada Ltd.
	5515 – 92 ST NW
	Edmonton, Alberta T6E 3A4
	Canada
	Tel: 001 (877) 746 6583
	E-mail: info@osmo.ca
	Manufacturer
	Osmo Holz und Color GmbH & Co. KG
	Affhüppen Esch 12
	D-48231 Warendorf
	Germany
Information department:	Product safety department
	Phone: +49 (0) 251 / 692 - 188
	Fax: +49 (0) 251 / 692 - 462
	e-mail: helmut.starp@osmo.de
1.4 Emergency telephone	
number:	24h-Emergency Phone Number:
	For Chemical Emergency, Spill; Leak; Fire Exposure or Accident Call Day or Nig
	within USA and Canada 1-800-424-9300
	Outside USA and Canada 001-703-527-3887 (WISAG FMO cargo Services Gmbh
	Co.KG)
Importer	Osmo Wood and Colour Canada Ltd.
	5515 – 92 ST NW
	Edmonton, Alberta T6E 3A4
	Canada
	Tel: 001 (877) 746 6583
	E-mail: info@osmo.ca

#### 2 Hazard identification

2.1 Classification of the substance or mixtureClassification according to Hazardous Products RegulationsFlam. Liq. 4 H227 Combustible liquid.

(Contd. on page 2)

CA



Printing date 11/15/2017

Reviewed on 08/28/2017

#### Trade name: Polyx®-Oil (Contd. of page 1) 2.2 Label elements Labelling according to Hazardous **Products Regulations** The product is classified and labeled according to the CLP regulation. Hazard pictograms Void Signal word Warning H227 Combustible liquid. Hazard statements If medical advice is needed, have product container or label at hand. **Precautionary statements** P101 P102 Keep out of reach of children. P103 Read label before use. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves / eye protection. P370+P378 In case of fire: Use for extinction: CO2, powder or water spray. P403 Store in a well-ventilated place. P501 Dispose of contents/container in accordance with local/regional/national/ international regulations. Additional information: Observe the general safety regulations when handling chemicals. Always wear a dust mask when sanding. Hazard description: WHMIS-symbols: B3 - Combustible liquid Classification system: NFPA ratings (scale 0 - 4) Health = 0Fire = 2Reactivity = 0Health = 0HMIS-ratings (scale 0 - 4) Fire = 2 Reactivity = 02.3 Other hazards Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard. **3** Composition/Information on ingredients

3.2 Mixtures			
Description:	Mixture of the substances	s listed below with nonhazardous additions.	
Dangerous components:			
64742-48-9 aliphatic hydroc	arbons, C10-C13	🚯 Asp. Tox. 1, H304; Flam. Liq. 4, H227	30-60%
Additional information:	94/69/EC (21st ATP).	The benzene content of the product is less th	an 0.1%.
	Classificatin or labeling a	s carcinogenic is not necessary.	
		(Conte	d. on page 3)



Printing date 11/15/2017

Reviewed on 08/28/2017

# Trade name: Polyx®-Oil

First aid measures	
4.1 Description of first aid measu	ires
General information:	Immediately remove any clothing soiled by the product.
After inhalation:	Supply fresh air; consult doctor in case of complaints.
After skin contact:	Immediately wash with water and soap and rinse thoroughly.
	If skin irritation continues, consult a doctor.
After eye contact:	Rinse opened eye for several minutes under running water.
After swallowing:	If swallowed, seek medical advice immediately and show this container or label.
	Do not induce vomiting; immediately call for medical help.
4.2 Most important symptoms and	d
effects, both acute and delayed	No further relevant information available.
4.3 Indication of any immediate	
medical attention and special	
treatment needed	No further relevant information available.

5.1 Extinguishing media Suitable extinguishing agents:	CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
5.2 Special hazards arising from the substance or mixture 5.3 Advice for firefighters	No further relevant information available.
Protective equipment:	No special measures required.

#### 6 Accidental release measures

6.1 Personal precautions,	
protective equipment and	
emergency procedures	Ensure adequate ventilation
	Keep away from ignition sources
6.2 Environmental precautions:	Inform respective authorities in case of seepage into water course or sewage system.
	Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for	
containment and cleaning up:	Warm water and cleansing agent
	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
6.4 Reference to other sections	See Section 7 for information on safe handling.
	See Section 8 for information on personal protection equipment.
	See Section 13 for disposal information.
	(Contd. on page 4)



Printing date 11/15/2017

Reviewed on 08/28/2017

		(Contd. of pa
Handling and storage		
7.1 Precautions for safe handling	No special precautions are necessary if used correctly.	
	Keep away from heat and direct sunlight.	
	Keep receptacles tightly sealed.	
	Use only in well ventilated areas.	
	Prevent formation of aerosols.	
Information about protection		
against explosions and fires:	No special measures required.	
7.2 Conditions for safe storage, in Storage: Requirements to be met by		
storerooms and receptacles:	Store in a cool location.	
Information about storage in one	Store only in the original receptacle.	
Information about storage in one common storage facility:	Do not store together with alkalis (caustic solutions).	
common storage jacuty.	Do not store together with aikans (caustic solutions). Do not store together with oxidizing and acidic materials.	
Further information about	Do not store together with oxidizing and acture materials.	
storage conditions:	None.	
sionage conantonsi	Keep receptacle tightly sealed.	
	Store in cool, dry conditions in well sealed receptacles.	
7.3 Specific end use(s)	No further relevant information available.	
no specific ena ase(s)	To further relevant information available.	

No further data; see item 7.
t
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
The lists that were valid during the creation were used as basis.
Do not eat, drink, smoke or sniff while working.
Do not carry product impregnated cleaning cloths in trouser pockets.
Use suitable respiratory protective device only when aerosol or mist is formed.
Not necessary if room is well-ventilated.
Short term filter device:
Gas filter EN 14387 Type A (organic gas / vapor (boiling point > 65 $^{\circ}$ C)).
(Contd. on page 5)



Printing date 11/15/2017

Reviewed on 08/28/2017

Material of gloves       T         Material of gloves       T         fill       fill         Penetration time of glove material       T         For the permanent contact gloves       made of the following materials         are suitable:       N         Eye protection:       T         9.1 Information on basic physical and chemical propert         9.1 Information on basic physical and General Information         Appearance:       F         Form:       F         Color:       A	and chemical properties
Material of gloves       T         Material of gloves       T         fill       fill         Penetration time of glove material       T         For the permanent contact gloves       T         made of the following materials       T         are suitable:       N         Eye protection:       T         Physical and chemical proper         9.1 Information on basic physical and         General Information         Appearance:         Form:       F         Color:       A	the preparation. Selection of the glove material on consideration of the penetration times, rate diffusion and the degradation The selection of the suitable gloves does not only depend on the material, but also further marks of quality and varies from manufacturer to manufacturer. As the pro- is a preparation of several substances, the resistance of the glove material can no calculated in advance and has therefore to be checked prior to the application. The exact break trough time has to be found out by the manufacturer of the protect gloves and has to be observed. Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling. <b>rties</b> Fluid
Material of gloves       I         Material of gloves       I         fill       is         Penetration time of glove material       I         For the permanent contact gloves       g         made of the following materials       are suitable:         Pysical and chemical propertion       I         9.1 Information on basic physical and General Information       Appearance:         Form:       F         Color:       A	Selection of the glove material on consideration of the penetration times, rate diffusion and the degradation The selection of the suitable gloves does not only depend on the material, but also further marks of quality and varies from manufacturer to manufacturer. As the pro- is a preparation of several substances, the resistance of the glove material can no calculated in advance and has therefore to be checked prior to the application. The exact break trough time has to be found out by the manufacturer of the protect gloves and has to be observed. Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling. The selection of the material: Properties Fluid
Material of gloves       T         fill       fill         is       fill         is       fill         is       fill         Penetration time of glove material       T         For the permanent contact gloves       g         made of the following materials       are suitable:         are suitable:       N         Eye protection:       C         Physical and chemical propert         9.1 Information on basic physical and General Information         Appearance:       F         Form:       F         Color:       A	diffusion and the degradation The selection of the suitable gloves does not only depend on the material, but also further marks of quality and varies from manufacturer to manufacturer. As the pro- is a preparation of several substances, the resistance of the glove material can no calculated in advance and has therefore to be checked prior to the application. The exact break trough time has to be found out by the manufacturer of the protect gloves and has to be observed. Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling.  rties Fluid Fluid
Material of gloves       I         file       file         Penetration time of glove material       I         For the permanent contact gloves       I         made of the following materials       I         are suitable:       N         Eye protection:       I         Physical and chemical proper       I         9.1 Information on basic physical and General Information       I         Appearance:       Form:       I         Form:       F         Color:       A	The selection of the suitable gloves does not only depend on the material, but also further marks of quality and varies from manufacturer to manufacturer. As the pro- is a preparation of several substances, the resistance of the glove material can no calculated in advance and has therefore to be checked prior to the application. The exact break trough time has to be found out by the manufacturer of the protect gloves and has to be observed. Nitrile rubber, NBR Recommended thickness of the material: $\geq 0.4$ mm Goggles recommended during refilling. <b>rties</b> Fluid
finition         Penetration time of glove material         For the permanent contact gloves         made of the following materials         are suitable:         Physical and chemical propertion         9.1 Information on basic physical and General Information         Appearance:         Form:       F         Color:       A	further marks of quality and varies from manufacturer to manufacturer. As the pro- is a preparation of several substances, the resistance of the glove material can no calculated in advance and has therefore to be checked prior to the application. The exact break trough time has to be found out by the manufacturer of the protect gloves and has to be observed. Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling. <b>rties</b> Fluid
is Penetration time of glove material T For the permanent contact gloves made of the following materials are suitable: N Eye protection: C Physical and chemical propert 9.1 Information on basic physical ar General Information Appearance: Form: F	is a preparation of several substances, the resistance of the glove material can no calculated in advance and has therefore to be checked prior to the application. The exact break trough time has to be found out by the manufacturer of the protect gloves and has to be observed. Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling. <b>rties</b> <b>nd chemical properties</b>
Penetration time of glove material       g         For the permanent contact gloves       g         made of the following materials       g         are suitable:       N         Eye protection:       G         Physical and chemical propert         9.1 Information on basic physical and General Information         Appearance:         Form:       F         Color:       A	calculated in advance and has therefore to be checked prior to the application. The exact break trough time has to be found out by the manufacturer of the protect gloves and has to be observed. Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling. <b>rties</b> <b>rties</b> Fluid
Penetration time of glove material T         For the permanent contact gloves         made of the following materials         are suitable:         Peretrained         Eye protection:         Physical and chemical propertion         9.1 Information on basic physical and General Information         Appearance:         Form:       Form:         Form:       Form:         Form:       Form:	The exact break trough time has to be found out by the manufacturer of the protect gloves and has to be observed. Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling. rties rties Fluid
For the permanent contact gloves         made of the following materials         are suitable:       N         Eye protection:       C         Physical and chemical property         9.1 Information on basic physical and         General Information         Appearance:         Form:       F         Color:       A	gloves and has to be observed.  Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling.   rties  nd chemical properties  Fluid
For the permanent contact gloves         made of the following materials         are suitable:       N         Eye protection:       G         Physical and chemical propert         9.1 Information on basic physical and         General Information         Appearance:         Form:       F         Color:       A	Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling. <i>rties</i> <i>and chemical properties</i> Fluid
made of the following materials are suitable:NEye protection:CPhysical and chemical property9.1 Information on basic physical and General Information Appearance: Form:Form:FColor:A	Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling. rties and chemical properties Fluid
are suitable:NEye protection:GPhysical and chemical property9.1 Information on basic physical and General Information Appearance: Form:Form:FColor:A	Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling. rties and chemical properties Fluid
Eye protection:       F         Eye protection:       C         Physical and chemical propert         9.1 Information on basic physical and         General Information         Appearance:         Form:       F         Color:       A	Recommended thickness of the material: ≥ 0.4 mm Goggles recommended during refilling. rties and chemical properties Fluid
Eye protection:OPhysical and chemical proper9.1 Information on basic physical and General InformationAppearance: Form:Form:Production:Appearance: Color:	Goggles recommended during refilling.  rties and chemical properties Fluid
Physical and chemical property 9.1 Information on basic physical and General Information Appearance: Form: F Color: A	rties and chemical properties Fluid
Form:FColor:A	
Color:	
	A second in a tangent and site and in a second in a second s
Odor: (	According to product specification
	Characteristic
Change in condition	
81 8 8	Undetermined.
Boiling point/Boiling range: U	Undetermined.
Flash point: >	> 65 °C (DIN 52231)
Ignition temperature: 2	240 °C
Auto igniting: P	Product is not selfigniting.
Danger of explosion: P	Product does not present an explosion hazard.
Explosion limits:	
-	0.6 Vol %
<b>Upper:</b> 7	7.0 Vol %
Vapor pressure at 20 °C: 1	1 hPa

*Water:* Not miscible or difficult to mix.

(Contd. on page 6)

C۸



Printing date 11/15/2017

Dermal

LD50

> 5000 mg/kg (rat) (OECD 402)

Reviewed on 08/28/2017

rade name: Polyx®-Oil	
	(Contd. of page
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	70-140 s (DIN 53211/4)
9.2 Other information	VOC Content: < 450 g/l
0 Stability and reactivity	
10.1 Reactivity	No further relevant information available.
10.2 Chemical stability	
Thermal decomposition /	
conditions to be avoided:	No decomposition if used according to specifications.
10.3 Possibility of hazardous	
reactions	Reacts with fabric soaked in the product (e.g. cleaning wool).
10.4 Conditions to avoid	No further relevant information available.
10.5 Incompatible materials:	No further relevant information available.
10.6 Hazardous decomposition	
products:	Carbon monoxide and carbon dioxide
	Nitrogen oxides (NOx)
Additional information:	
U U	Warning:
	Wash out any used cloth impregnated with this product immediately after use or sto
	in an airtight container (danger of self-ignition)
1 Toxicological information	
11.1 Information on toxicologic	al effects
Acute toxicity:	Based on available data, the classification criteria are not met.
LD/LC50 values that are relevant	t for classification:
64742-48-9 aliphatic hydrocarb	ons, C10-C13
Oral LD50 > 5000 mg	/kg (rat) (OECD 401)

Inhalative LC50 / 4h	21 mg/l (rat) (OECD 403)
Primary irritant effec	t:
on the skin:	At long or repeated contact with skin it may cause dermatitis due to the degreasing
	effect of the solvent.
on the eye:	Based on available data, the classification criteria are not met.
Sensitization:	Based on available data, the classification criteria are not met.
	(Contd. on page 7)



Printing date 11/15/2017

Reviewed on 08/28/2017

(Contd. of page 6)

3

1

Κ

## Trade name: Polyx®-Oil

Additional toxicological information:

Carcinogenic categories

IARC (International Agency for Research on Cancer)

112926-00-8 Precipitated silica (Silica-Amorphous)

14808-60-7 Quartz (SiO2)

NTP (National Toxicology Program)

14808-60-7 Quartz (SiO2)

#### 12 Ecological information

#### 12.1 Toxicity

Aquatic toxicity:		
64742-48-9 aliphatic hydrocarbons, C10-C13		
EC50 / 48h	> 1000 mg/	l (daphnia) (OECD 202)
EC50/ 72h	> 1000 mg/	1 (algae) (OECD 201)
LC50 / 96h	> 1000 mg/	1 (fish) (OECD 203)
Biolog. Abbaubarkeit	(leicht abb	aubar)
12.2 Persistence and degradability No further relevant information available.		
12.3 Bioaccumulative	potential	No further relevant information available.
12.4 Mobility in soil		No further relevant information available.
Additional ecological	information	<i>ı:</i>
General notes:		Water hazard class 1 (Self-assesment): slightly hazardous for water
12.5 Results of PBT and vPvB assessment		
PBT:		Not applicable.
vPvB:		Not applicable.
12.6 Other adverse eff	fects	No further relevant information available.

#### 13 Disposal considerations

13.1 Waste treatment methods Recommendation:	Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
Uncleaned packagings:	Disposal must be made according to official regulations.
Recommendation:	(Contd. on page 8)



Printing date 11/15/2017

Reviewed on 08/28/2017

		(Contd. of pa
Transport information		
14.1 UN-Number		
DOT, TDG, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		
DOT, TDG, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
DOT, TDG, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
DOT, TDG, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Anne	ex II of	
MARPOL73/78 and the IBC Code	Not applicable.	
Transport/Additional information:	Not dangerous according to the above specifications.	
UN "Model Regulation":	Void	
Regulatory information		
15.1 Safety, health and environmental reg Sara	gulations/legislation specific for the substance or mixture	

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

TSCA (Toxic Substances Control Act):

All ingredients are listed.

Canadian substance listings:

Canadian Domestic Substances List (DSL)

All ingredients are listed.

Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

Canadian Ingredient Disclosure list (limit 1%)

None of the ingredients is listed.

(Contd. on page 9)



Printing date 11/15/2017

Reviewed on 08/28/2017

de name: Polyx®-Oil		
15.2 Chemical safety assessment:	A Chemical Safety Assessment has not been carried out. (Contd. of page	
Other information		
This information is based on our pr features and shall not establish a leg	resent knowledge. However, this shall not constitute a guarantee for any specific produ gally valid contractual relationship.	
Relevant phrases	H227 Combustible liquid.	
F asos	H304 May be fatal if swallowed and enters airways.	
Department issuing SDS:	product safety department	
Contact:	Hr. Dr. Starp	
Date of preparation / last revision	11/15/2017 / -	
Abbreviations and acronyms:	IMDG: International Maritime Code for Dangerous Goods	
	DOT: US Department of Transportation	
	IATA: International Air Transport Association	
	GHS: Globally Harmonised System of Classification and Labelling of Chemicals	
	EINECS: European Inventory of Existing Commercial Chemical Substances	
	ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)	
	NFPA: National Fire Protection Association (USA)	
	HMIS: Hazardous Materials Identification System (USA)	
	WHMIS: Workplace Hazardous Materials Information System (Canada)	
	LC50: Lethal concentration, 50 percent	
	LD50: Lethal dose, 50 percent	
	PBT: Persistent, Bioaccumulative and Toxic	
	vPvB: very Persistent and very Bioaccumulative	