

## **MATERIAL SAFETY DATA SHEET**

Product Name/Code			HMIS CODES				
SAMAN WATER-BASED STAINS / TEW SERIES			health 1 flammability 0 reactivity 0				
Section 1 Product and Company Ident	ification						
Manufacturer's name			Emergency Telephone Number				
Saman 3777472 Canada inc.			819-751-235	0			
Address (Number, Street, City, State and ZIP Code)			Telephone Number for Information				
1235, rue de L'Acadie Victoriaville (Québec) Canada G6T 1W4			819-751-2350				
Date May 2011			Prepared by Y	van Désilets			
Section 2 Hazardous Ingredients/Ident	ity Informa	ation					
HAZARDOUS COMPONENTS NAME / CAS NO.		WT %	OSHA PEL	ACGIH TLV	ORAL LD50	(RAT)	DERMAL LD50 (RABBIT)
2-butoxyethanol (EB) / 111-76-2		0-0.5	50 ppm	25 ppm	1480 mg/l		220 mg/kg
2-(2-methoxyethoxy)ethanol (DM) / 1	11-77-3	0.1-2.5	n/a	n/a	5500 mg/l	kg	9400 mg/kg
1,2-propanediol / 57-55-6		30-60	n/a	5 mg/m <sup>3</sup>	20 mg/kg		20.8g/kg
carbon black / 1333-86-4		0-5	3.5 mg/m <sup>3</sup>	3.5 mg/m <sup>3</sup>	>8000 mg/	/kg	n/a
Section 3 Physical/Chemical Characte		0-5	3.5 mg/m <sup>3</sup>	3.5 mg/m <sup>3</sup>	>8000 mg,	/kg	n/a
Section 3 Physical/Chemical Characte  Appearance and Odor coloured liquid, r	nild odor				>8000 mg/		n/a
Section 3 Physical/Chemical Characte  Appearance and Odor coloured liquid, r  Specific Gravity (H O = 1)	nild odor	1.3	Viscosity Zahn c	sup #2 (seconds)	>8000 mg.	n/a	
Appearance and Odor coloured liquid, respectific Gravity (H <sub>O</sub> O = 1)  pH	nild odor 1.0-	1.3		cup #2 (seconds)	>8000 mg/	n/a 67-9	n/a 00 ± 1
Appearance and Odor coloured liquid, respectific Gravity (H O = 1)  OH  Boiling Point (°F)	nild odor 1.0-1 8.0-8 212-	1.3 8.5 -385	Viscosity Zahn c	eup #2 (seconds)	>8000 mg/	n/a 67-9 n/a	00 ± 1
Appearance and Odor coloured liquid, r Specific Gravity (H O = 1) pH Boiling Point (°F) Vapor Pressure (mm Hg)	nild odor 1.0- 8.0-8 212- 17.5	1.3 8.5 -385 -4 (H <sub>2</sub> O)	Viscosity Zahn c % Volatile by We Melting Point (°F	eup #2 (seconds)	>8000 mg/	n/a 67-9 n/a	
Appearance and Odor coloured liquid, respecific Gravity (H O = 1) pH Boiling Point (°F) Wapor Pressure (mm Hg) Evaporation Rate (Butyl Acetate = 1)	nild odor 1.0- 8.0-8 212- 17.5	1.3 8.5 -385	Viscosity Zahn of % Volatile by Wo Melting Point (°F Vapor Density (A	eup #2 (seconds)	>8000 mg/	n/a 67-9 n/a 4.15	00 ± 1
Appearance and Odor coloured liquid, respectific Gravity (H O = 1) pH Boiling Point (°F) Vapor Pressure (mm Hg) Evaporation Rate (Butyl Acetate = 1) Solubility in Water miscible	nild odor 1.0- 8.0-8 212- 17.5 0.07	1.3 8.5 -385 -4 (H <sub>2</sub> O)	Viscosity Zahn of % Volatile by Wo Melting Point (°F Vapor Density (A	eup #2 (seconds)	>8000 mg/	n/a 67-9 n/a 4.15	00 ± 1
Appearance and Odor coloured liquid, respecific Gravity (H <sub>O</sub> O = 1)  pH  Boiling Point (°F)  Vapor Pressure (mm Hg)  Evaporation Rate (Butyl Acetate = 1)  Solubility in Water miscible  Section 4 Fire and Explosion Hazard D  Flash Point (Method Used)  n/a	nild odor 1.0- 8.0-8 212- 17.5 0.07	1.3 8.5 -385 -4 (H <sub>2</sub> O)	Viscosity Zahn of % Volatile by Wo Melting Point (°F Vapor Density (A	eight  AIR = 1)		n/a 67-9 n/a 4.15	00 ± 1
Appearance and Odor coloured liquid, respecific Gravity (H O = 1) pH Boiling Point (°F) Vapor Pressure (mm Hg) Evaporation Rate (Butyl Acetate = 1) Solubility in Water miscible  Section 4 Fire and Explosion Hazard D Flash Point (Method Used) Extinguishing Media foam, carbon dioxid Use water spray to	nild odor 1.0- 8.0- 212- 17.5 0.07	1.3 8.5 -385 -4 (H <sub>2</sub> O) (EB)	Viscosity Zahn c % Volatile by We Melting Point (°F Vapor Density (A VOC (g/l)	eight  AIR = 1)		n/a 67-9 n/a 4.15 250	00 ± 1
Specific Gravity (H <sub>2</sub> O = 1) pH  Boiling Point (°F)  Vapor Pressure (mm Hg)  Evaporation Rate (Butyl Acetate = 1)  Solubility in Water miscible  Section 4 Fire and Explosion Hazard D  Flash Point (Method Used)  Flash Point (Method Used)  The section of the sect	1.0-1 8.0-6 212- 17.5 0.07	1.3 8.5 385 4 (H <sub>2</sub> O) (EB)	Viscosity Zahn c % Volatile by We Melting Point (°F Vapor Density (A VOC (g/l)	eup #2 (seconds) eight E) AIR = 1)	/a	n/a 67-9 n/a 4.15 250	00 ± 1
Appearance and Odor coloured liquid, r Specific Gravity (H O = 1) pH Boiling Point (°F) Vapor Pressure (mm Hg) Evaporation Rate (Butyl Acetate = 1) Solubility in Water miscible  Section 4 Fire and Explosion Hazard D Flash Point (Method Used) Extinguishing Media foam, carbon dioxid Use water spray to	1.0-1 8.0-6 212- 17.5 0.07	1.3 8.5 385 4 (H <sub>2</sub> O) (EB)	Viscosity Zahn of Wolatile by We Melting Point (°F Vapor Density (A VOC (g/l))  Flammable Limit Dwder area.	eup #2 (seconds) eight E) AIR = 1)	/a	n/a 67-9 n/a 4.15 250	00 ± 1

Section 5 Reactivity Data			2/2
Stability stable under normal s	storage and u	ise	Conditions to Avoid none known
Incompatibility (Materials to Avoid)	xidizing age	nts, strongly alkalin	e and strongly acid materials
Hazardous Decomposition or Byprodu	icts Therma	decomposition will	produce carbon dioxide and may yield carbon monoxide,
		of nitrogen, etc.	,
Hazardous Polymerization will not			Conditions to Avoid n/a
*****	oodai		1,74
Section 6 Health Hazard Data			
Route(s) of Entry eye and skin o	ontact, inhal	ation, ingestion	
Health Hazards This product m	av be an eve	irritant. Prolonged	or repeated contact may cause skin irritation. Prolonged
· · · · · · · · · · · · · · · · · · ·	-		neadache, dizziness and respiratory tract irritation. Ingestion
	-	irritation, nausea ar	• • • • • • • • • • • • • • • • • • • •
Carcinogenicity no			
Medical Conditions			
	none genera	lly recognized	
Emergency and First Aid Procedures	Eye:	Check for and rem	ove any contact lenses. Immediately flush with plenty of
	•	water. Get medica	
	Skin:	Remove contamina	ated clothing. Wash skin thoroughly with soap and water.
	Inhalation:		ir. Administer artificial respiration if necessary. Get medical
		aid.	
	Ingestion:	Do not induce vom	iting. Give 1-2 glasses of water to dilute stomach contents.
			vomiting occurs spontaneously, keep head below hips to of liquid into lungs. Never give anything by mouth to an on.
Section 7 Precautions for Safe	Handling and	d Use	
Steps to Be Taken in Case Material Is	Released or Sp	Stop leak if wi	thout risk. Prevent entry into drains or watercourses. Absortnaterial and put in an appropriate waste disposal.
Waste Disposal Method Dispose	of in accorda	nce with local, state	e and federal environmental control regulations.
Precautions to Be Taken in Handling	and Ctaring		d when not in use. Transfer only to approved containers wit
	CC		oriate labeling. Store in a cool well-ventilated area. Keep from
Section 8 Exposure Controls a	nd Personal	Protection	
	equate ventila sure limit(s).	ation. Local exhaus	t in addition to general room ventilation may be required to
Porconal Protection		ad with normal use	in well-ventilated area
ixespiratory.	-		advised for poorly ventilated areas.
Eye/Face:		ses, splash googles	
Skin:			
JMII.		ed clothing before re	
Work/Hygienic Practices Do not s			
			s, beverages, tobacco products or cosmetics next to materia
vvaSii iii	anus anu iau	e carefully after wo	IN.

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.