CARVER S.r.l.

Via Giovanni XXIII, 36 20090 Rodano (MI) ITALY Tel. (02) 95.00171 (r.a.) Fax (02) 95.320.921 internet: www.carver.it



AZIENDA CON SISTEMA DI GESTIONE PER LA QUALITÀ CERTIFICATO DA DNV =UNI EN ISO 9001:2000=

AZIENDA CON SISTEMA DI GESTIONE AMBIENTALE CERTIFICATO DA DNV = UNI EN ISO 14001:2004 =

TECHNICAL DATA SHEET

rev. 03 30/11/2007

DETEROL (wood soap)

code SO8203

TECHNICAL DATA (with room temperature of +23°C and 65% of relative air humidity)

Appearance yellow-brown, clear liquid Viscosity 15° F4 \pm 3 $^{\circ}$ F4 pH 9.5 ± 1.0 Specific weight 1.00 ± 0.02 Dilution 1:100 Average yield of the diluted product $20-30 \text{ m}^2/\text{liter}$

DESCRIPTION

Wood soap on the base of coconut and soya oil derivatives, especially developed for the maintenance of oiled wooden floors. DETEROL nourishes and cleans the wood, is waterdilutable and suitable for professional as well as for domestic use.

PACKAGING

1-litre plastic bottles.

DIRECTIONS

Dilute the product with water approx. 1: 100, then wipe the floor using a soft cloth or a mop previously soaked in the solution and thoroughly wrung. It is advisable to use two buckets: one with the detergent solution, the other with clear water, to regularly rinse the cloth or mop to remove dirt.

LET THE FLOOR DRY WITHOUT RINSING!

NOTICE

- The maintenance with DETEROL can start not before 7 10 days after the impregnation treatment.
- Dilute DETEROL only in water.
- **Attention!** As a general rule, wood floors should not be flooded with plenty of liquid, but wiped with moist clothes or mops.

Protect from freezing!

If the original unopened container is stored in a cool and dry place, the product will keep for at least 12 months.

N.B. The information contained in this technical data sheet is to the best of our knowledge and experience. Since the conditions of use are beyond our control, no warranty is given or implied.