

Secondo Mono

Finishing Oil for Wooden Floors

Secondo Mono is an oil designed to be applied on floors or other wooden surfaces. Secondo Mono oil waterproofs and resists to abrasion, it can be used alone or with Uno colored oil.

The *Colorless* version provides a honeyed tone and can be used on all types of wood.

The *Natural* version is used to preserve the whiteness of white woods (white pine, maple, cedar, spruce, beech, aspen) or white and gray colored wood (e.g. *White* or *Gray* Uno coloring oil). Do not use the *Natural* version on open grain woods (oak, walnut, mahogany, elm) or colored woods (except for white or gray).

Preparation

Shake well before and while using. Apply at a temperature above 15 °C. Wood must be sanded with 100 or 120 grit paper. Vacuum to dust off.

Prior to application on maple wood, wet the wood, let dry 2 hours and lightly sand with a 220 grit sandpaper.

Application

Apply with a stain applicator, a cloth or a stain pad. **After 5 to 15 minutes, completely wipe off the surface with a cloth to remove any excess oil.**

For an application on furniture and woodwork, it is recommended to use 600 or 800 grit sandpaper between coats.

Secondo Mono can be polished using a polishing machine, using a red or green buffer.

Number of Coats

On Uno treated wood : 1 coat

On untreated wood : 1 to 2 coats

On heavy traffic surfaces such as kitchen countertops and work area, it is recommended to apply an additional coat.



- One single coat required
- Good abrasion resistance
- Waterproofs wood surfaces
- Great coverage
- Leaves no film on the wood surface
- Lets the wood vein show through
- Easy to apply
- Easy care
- Lets the wood breath
- Low odor

Project Types

Floors, furniture, kitchen cabinets, countertops, islets, interior windows and doors, woodwork, walls and ceilings.

Surface Types

Wood, cork

Compatibility

- Can be applied on : Wood oil, wood stain
- Can be covered with : Wood oil, wood varnish, wood wax

Durability

Heavy traffic : 2 to 3 years

Low traffic : 5 to 7 years

Drying Time

- Between coats : 24 hours
- Careful use : 24 hours
- Put back rugs and furniture : 7 days
- First damp cleaning : 10 days

Covering

Softwoods: 150 to 225 sq ft / L

Hardwoods: 225 to 360 sq ft / L

Maintenance

Bonito soap, Sancio protector

Tools Cleaning

Oil thinner

Storage

Keep in an airtight container.

Composition

Safflower oil, tung oil, linseed oil, vegetal wax, isoparaffin, siccative.

Residues Disposal

Consult your municipality to properly dispose the remains of this product.

DANGER OF COMBUSTION - Keep out of reach of children.
Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

Warranty

Tembi products guarantee the quality of its products. They comply with the description given in the data sheets and proper labels for their intended use, in accordance with the instructions indicated by the company. However, since the manufacturer has no control over the circumstances, methods and usage conditions, this warranty covers only the high quality of Prato-Verde products.

Sheen

Satin matt (5 à 7 %)

VOCs

299 g / L

Sizes

- 20 ml (sample)
- 237 ml
- 946 ml
- 3.78 L
- 18.9 L

Colors

- Colorless
- Natural

Origin

Italy